



WZ-78

Folding door

PRODUCT PARAMETES

Water tightness	450 pa
Air tightness	1.8 m³/(m·h)
Wind pressure resistance	4.5K pa
Sound insulation performance	30 dB
U-Factor(U.S./1-P)	0.38
SHGC	0.22

Glass: Double Tempered Glass with argon ags
5mm+27A+5mm
(PVDF Aluminum Strip Between double glass)

Profile: 6063-T5 aluminum profile

Profile Thinckness: 1.6MM

Frame width: 78MM

Handle: Kerssemerberg Handle in Black or Sliver

Hinge: Kerssemerberg Hinge in Black or Sliver

Lock point: Kerssemerberg Specialized locking point

Insulation strip: Standard BAIYUNYILE insulation strip

Optional package: New 47 Pack/70 Pack/75 Pack/100 Pack

Sealing material: EPDM rubber strip

Available Size: Opening Panel (Width:500-800/Height:1000-2800)

PRODUCT PROCESS

· Adopting internal and external gluing process



WZ-80

Folding door

PRODUCT PARAMETES

Water tightness	350 pa
Air tightness	1.8 m³/(m·h)
Wind pressure resistance	4.5K pa
Sound insulation performance	35 dB
U-Factor(U.S./1-P)	0.38
SHGC	0.22

Glass: Double Tempered Glass with argon ags
5mm+20A+5mm
(PVDF Aluminum Strip Between double glass)

Profile: 6063-T5 aluminum profile

Profile Thinckness: 2.0MM

Frame width: 80MM

Handle: CMECH Handle in Black or Sliver

Hardware: CMECH Hinge in Black or Sliver

Lock point: CMECH Specialized locking point

Insulation strip: Standard BAIYUNYILE insulation strip

Optional package: New 47 Pack/70 Pack/75 Pack/100 Pack

Sealing material: JIANGYINHAIDA rubber strip

Available Size: Opening Panel (Width:500-850/Height:1000-3000)

PRODUCT PROCESS

· Adopting internal and external gluing process